

Building User Interfaces

React Native 3


Advanced Concepts

Professor Bilge Mutlu

What we will learn today?


- » Accessible Building
- » Storing data using AsyncStorage
- » Theming Libraries
- » Accessing and Using Sensor Data
- » App Lifecycle using AppState
- » Assignment Preview

TopHat Attendance



TOP HAT

TopHat Questions




TOP HAT

Accessible Building

Accessibility in Web Technologies¹

From the *three-layered cake* to the *Peanut M&M*:



By Dennis Lembree based on illustration by Dave Stewart

¹[Image source](#)

Accessible Rich Internet Applications (ARIA)²

aria is a set of HTML attributes that make web components available to assistive technologies.

```
<div id="percent-loaded" role="progressbar" aria-valuenow="75"  
    aria-valuemin="0" aria-valuemax="100">  
</div>
```

²[MDN Web Docs: ARIA](#)

Accessibility in React Native³

RN provides us with access to assistive technologies that mobile platforms provide (e.g., VoiceOver on iOS or TalkBack on Android) through component attributes.

```
<View accessible={true}>  
  <Text>List item one</Text>  
  <Text>List item two</Text>  
</View>
```

means that all things inside get enumerated

³React Native Accessibility

React Native Accessibility Properties

`accessible` attribute indicates whether the component is an accessibility element and, if so, groups its children in a single selectable component.

`accessibilityLabel` attribute defines screen reader descriptions of components. *← doesn't have to be visible on screen*

`accessibilityHint` attribute helps users understand what will happen if they perform the action on the accessibility element.

React Native Accessibility Actions

Standard, e.g., `magicTap`, `escape`, `activate`, `increment`, `decrement`, `longpress`, or custom actions, handled by `onAccessibilityAction`.

```
onAccessibilityAction={ (event) => {  
  switch (event.nativeEvent.actionName) {  
    case 'longpress':  
      // take action  
  
      ...  
    }  
  }  
}}
```

AsyncStorage

What is AsyncStorage?

AsyncStorage is a simple, unencrypted, persistent, key-value storage system that is global to the app.

Four key features:

1. **Simple:** Core functionality involves `set` and `get` methods.
2. **Unencrypted:** Access is controlled by location access.
3. **Persistent:** Data is saved until it is explicitly deleted.
4. **Global:** Saved data is global to the app.

How does it work?

We use the AsyncStorage JS library:


```
import AsyncStorage from '@react-native-community/async-storage';
```

Through RN Bridge, the corresponding native code library will store the data in an appropriate format, in a dictionary or files in iOS and in a database in Android.

All AsyncStorage operations are asynchronous and therefore return a Promise.

Saving Data

```
storeData = async () => {  
  try {  
    await AsyncStorage.setItem('@storage_Key', 'stored value')  
  } catch (e) {  
    // saving error  
  }  
}
```



item key

item value

Retrieving Data

```
getData = async () => {  
  try {  
    const value = await AsyncStorage.getItem('@storage_Key')  
    if(value !== null) {  
      // value previously stored  
    }  
  } catch(e) {  
    // error reading value  
  }  
}
```

gets data



Other operations⁴

`removeItem(key)` removes the item that corresponds to a key.

`mergeItem(key)` merges an existing key value with an input value.


`clear()` erases all AsyncStorage. *← would do on logout, for example*

`getAllKeys()` retrieves all keys for your app.

`multiGet(keys)`, `multiSet(keys, values)`, `multiRemove(keys)`, `multiMerge(keys, values)` are batch operations for array data.

⁴[More information on RN AsyncStorage](#)

TopHat Quiz



TOP HAT

Theming in React Native

Popular Theme Libraries and Toolkits

>> NativeBase

>> React Native Elements

NativeBase^{5 6}

You can use projects in your projects
Check out

For iOS and Android.


Customized using NativeBase Customizer.

Different themes using
StyleProvider.

```
<Button light style={{borderRadius:8}}>  
  <Text>Contact Us</Text>  
</Button>
```

⁵ Image source

⁶ See example in Expo



Importing themes:

```
import getTheme from './native-base-theme/components';  
import material from './native-base-theme/variables/material';
```

Applying themes using `getTheme()`:

```
<StyleProvider style={getTheme(material)}>  
  <Container>  
    <Content>  
      ...  
    </Content>  
  </Container>  
</StyleProvider>
```

Sensors

Sensor Libraries

Two options:

1. React Native sensors library: `react-native-sensors`
2. Expo sensors library: `expo-sensors`

Expo Sensors Library

Provides access to device sensors through specific components:

`Accelerometer`: provides access to the accelerometer sensor, which captures displacement in 3D.

`Barometer`: provides access the device barometer sensor, which captures changes in air pressure.

`Gyroscope`: provides access the device gyroscope sensor, which captures changes in rotation in 3D space.

`Magnetometer`: provides access the device magnetometer sensor, which measures changes in the magnetic field.

`MagnetometerUncalibrated`: provides access to uncalibrated raw values from the magnetometer.

`Pedometer`: Provides step count from the native sensor libraries.

How to Access Sensor Data

Install the sensor library:

```
expo install expo-sensors
```

Import the sensor component:

```
import { Accelerometer } from 'expo-sensors';
```

Check if the sensor is available:

```
Accelerometer.isAvailableAsync() // returns true or false
```


↑ asynchronous

Create listener for sensor events:

Accelerometer.addListener(listener)

Best practice is to create subscribe and unsubscribe functions:

```
_subscribe = () => {  
  this._subscription = Accelerometer.addListener(accelerometerData => {  
    this.setState({ accelerometerData });  
  });  
};
```



To remove listeners for sensor events:

`Accelerometer.removeAllListeners()`

To subscribe to updates to the sensor data at specified intervals:

`Accelerometer.setUpdateInterval(intervalMs)`

Access to Other Hardware

Camera using `expo-camera` renders a preview of the front or the back camera.

Battery using `expo-battery` provides battery information.

Haptics using `expo-haptics` provides haptic feedback using the Taptic Engine on iOS and Vibrator system service on Android.

Audio using `expo-av` provides basic audio playback and recording.

Brightness using `expo-brightness` allows getting and setting screen brightness.

App Lifecycle Using AppState

The Problem

Everything we have been doing so far assumes that our app is loaded on the screen and is running as a foreground process.

We need to be able to perform background processes or safely save the user's data in case the OS suspends it or the user quits it.

The Solution

AppState provides information on the current state of the app:

- >> `active` indicates that the app is running in the foreground
- >> `background` indicates that the app is running in the background
- >> `inactive` indicates that the app is transitioning between foreground and background


```
import {AppState} from 'react-native';
```

```
state = { appState: AppState.currentState};
```

```
componentDidMount() {
```

```
  AppState.addListener('change', this._handleAppStateChange);
```

```
}
```

```
_handleAppStateChange = (nextAppState) => {
```

```
  if (this.state.appState.match(/inactive|background/) && nextAppState === 'active') {
```


```
    // Do something
```

```
  }
```

```
  this.setState({appState: nextAppState});
```

```
};
```

you should unsubscribe on dismount



Example Background Process

BackgroundFetch from expo-background-fetch allows performing background fetch tasks using the TaskManager Native API.

BackgroundFetch.registerTaskAsync(taskName, options)

Assignment Preview

React Native 3 Requirements

- » Be able to add a meal to a day
- » Be able to add foods to meals
- » Summarize (aggregate) stats for meals based on foods
- » Hook up stats in day view for nutritional data (aggregated over meals/foods from that day)
- » Allow users to track their stats over a the past 7 days
- » Clean/Clear/Attractive interface

Some Notes

1. Using endpoint for foods (not limited to these):

<https://mysqlcs639.cs.wisc.edu/foods/>

1. pluralize package to properly format food items:

```
pluralize('test', 1, true) //=> "1 test"
```

```
pluralize('test', 5, true) //=> "5 tests"
```

What did we learn today?

- » Accessible Building
- » Storing data using AsyncStorage
- » Theming Libraries
- » Accessing and Using Sensor Data
- » App Lifecycle using AppState
- » Assignment Preview